

49 - Data Backups

cp used to archive a full directory

```
cp -a SrcDirectory DstDirectory
```

Tar backup program:

Syntax:

```
tar [options] ArchiveFile File_or_Directory
```

Creating or extracting .tgz or .tar.gz archive files

```
tar xzvf ArchiveFile [-C Pfad]
```

x=extract z=uncompress v=verbose f=file

```
tar czvf ArchiveFile [-C Pfad] c=create z=compress
```

```
tar tzf ArchiveFile (Shows the content of a tar archive)
```

```
tar rvzf ArchiveFile File
```

(Insert a file in a tar archive)

eg.

```
tar cvf archive1.tar file1 file2
```

(Creates an archive and inserts file1 & file2)

```
tar rvf archive1.tar datei3
```

(inserts datei3 in archive1.tar)

```
tar tzf archive1.tar.gz
```

(Shows the content of archive1.tar.gz)

```
tar xzvf archive1.tar.gz file2
```

(extracts file2 from archive1.tar.gz)

Using multiple removable media

```
tar -Mcvf /dev/fd0 /sourcedir
```

(Creates a backup of a directory onto multiple floppies)

```
tar -Mxvf /dev/fd0
```

(extract all files from a backup made on multiple floppies into the current directory)

Using separate gzip compression

```
gzip archive1.tar
```

(compresses archive1.tar -> archive1.tar.gz)

```
gzip -d archive1.tar.gz
```

(decompresses archive1.tar.gz)

Using extra bz2 compression

Creating a .tar.bz2 compressed file

```
tar fvcj filename.bz2 /dir_to_compress
```

Extracting a .tar.bz2 file

```
tar fvxj filename.bz2
```

bzip2 file (creates a filename.bz2, the original is erased)

bunzip2 file.bz2 (decompress the file.bz2, the original is erased)

- **cpio backup program.**

```
cpio -i (--extract) -v -I Device or File
```

```
cpio -t (--list)
```

```
find . | cpio -o (--create) -v (--verbose) -O Device_or_File
```

afio is like cpio but uses compression -Z (gzip)

Other backup programs

tob (Tape Oriented Backup)

amanda (Advanced Maryland Automated Network Disk Archiver)

arakaia (Commercial and GPL graphic backup program)

Special tips and tricks of backing-up

- To make a backup of a directory with the date integrated in the filename:

```
tar fvcz /bk/backup$(date '+F_%H.%M.%S').tar.gz /home
```

will create the file(for example)

```
/bk/backup2003.05.09-12.20.27.tar.gz
```

containing the whole /home directory and its subdirectories.

- To copy a full image of a partition to a file on another host:

Uncompressed:

```
dd if=/dev/hda1 | ssh remotehost dd of=imagefile
```

Compressed:

```
dd if=/dev/hda1 | bunzip2 -c | ssh remotehost dd of=image.bz2
```

- To copy a whole directory without any file modifications:

```
(cd /sourceDir && tar cf - . ) | (cd /destDir && tar xvfp -)
```